# Mac Water Coolers

The Mac is one of our most reliable coolers that will give your office or home years of service.

Available in hot & cold or cook & cold and with or without a refrigerator, this water cooler is an excellent addition to your kitchen, living room or private office.

#### MODELS >

MSHC-200 Hot & Cold Standard MSCC-200 Cook & Cold Standard MRHC-200 Hot & Cold with Refrigerator MRCC-200 Cook & Cold with Refrigerator

Bottle and cup dispenser sold separately.

# Enjoy Refreshing & Pure Water Everyday!



Clear Solutions. Pure Service.



		STANDARD	
Product Name		HOT & COLD Water Dispenser	COOK & COLD Water Dispenser
Model		MSHC-200	MSCC-200
Dimension		300 W x 330 D x 970 H (mm)	
Weight		18 kg	17 kg
	Current	5.50 A	
COLD	Temp Control	AUTO	
	Tank	4 L (Stainless Steel Tank)	
	Capacity	5 L/h (6°C - 10°C)	
H O T	Fuse	BIMETAL	N/A
	Temp Control	AUTO	
	Tank	1.92 L (Stainless Steel Tank)	
	Capacity	10 L / h (85°C - 93°C)	
Power		115V/60Hz or 220V/50-60Hz	

Product Name		HOT & COLD Water Dispenser	COOK & COLD Water Dispenser
Model		MRHC-200	MRCC-200
Dimension		300 W x 330 D x 970 H (mm)	
Weight		18 kg	17 kg
Current		5.50 A	
С	Temp Control	AUTO	
0	Tank	4 L (Stainless Steel Tank)	
Ď	Capacity	5 L / h (6°C - 10°C)	
	Fuse	BIMETAL	N/A
Н	Temp Control	AUTO	
O T	Tank	1.92 L (Stainless Steel Tank)	
	Capacity	10 L/h (85°C - 93°C)	

#### Color

White

#### Cabinet

High-impact, high -gloss ABS materials for the top and front panels. Electric zinc-coated with high-polymer, polyester resin metal sheets for side panels. Both materials can be easily cleaned and maintained. The sides have mounting holes for cup dispensers.

#### Refrigeration Unit

Air convection-cooled condenser, internally spring mounted, hermetically-sealed compressor with automatic overload protection. No need for lubrication. Environment-friendly, R134a refrigerant is accurately controlled by precise capillary tube.

# Hot Water Tank (for Models MSHC-200 & MRHC-200)

1.92L capacity, type 304 stainless steel hot water tank with type 316 stainless steel 500W bottom heating element. Fast-draining, stainless steel tubing with drain nut. Tank is insulated with fire-retardant materials for good heat transfer and to save energy. The hot water is controlled between 85°C to 93°C by an automatic hot water themostat. The system is protected by a heat limiter in the event of automatic thermostat failure. On-off switch is conveniently located at the back of the cooler.

# **Cold Water Tank**

4L capacity, type 304 stainless steel cold water tank with external copper refrigerant coil evaporator. Removable expanded polystyrene insulation. The cold water is controlled between 6°C to 10°C by an automatic cold water thermostat that is easily accessible at the back of the cooler.

#### Electrical

Available 100V 50/60Hz, 110-115V 60Hz and 220-240V 50/60Hz with fuse protection. Unit comes with 1.80m power cord set with choice of plug. UL listed or CE certified.

#### **Pilot Lamps**

LED lights located at the display name plate of the front panel indicate whether the hot water and cold water are functioning.

# **Drip Tray**

Made of high-impact, ABS materials. Removable and concealed lift-out design with detachable, anti-splash grill.

#### Faucets

Soft touch faucets for both hot or cold or room temperature water. The hot water has a lock to protect children.

#### **Custom Logo**

Company logo or brand name can be silk-screen printed on the display name plate, drip tray, or front panels.

#### Quality & Warranty

All surfaces in contact with water are food-grade and would resist any known sanitizers. This model is manufactured under strict quality control, 100% tested in the assembly line, and complies with UL and CE standards. Warranty is 18 months for the unit and 48 months for the refrigeration system. (Please refer to the Warranty Card at the back of the User's Manual for details.)

# Available with Refrigerator

The unit with refrigerator has a bigger compressor to allow for good cooling. (See inset picture)



Clear Solutions. Pure Service.

P.O. Box 6416, Concord, CA 94524 USA Tel 925.686.1864 / Fax 925.686.1865 sales@americanultrafil.com / www.americanultrafil.com