

Rio Water Coolers



The Rio Cooler has an appealing design that will appeal to your discerning taste. It will complement beautifully with your existing furniture or appliances. It is available in hot & cold or cook & cold.

◀ MODELS

RSHC-300 Hot & Cold Standard
RSCC-300 Cook & Cold Standard

Bottle sold separately.

*Enjoy Refreshing
& Pure Water Everyday!*



Clear Solutions. Pure Service.

Product Specifications & Features

Rio

STANDARD		
Product Name	HOT & COLD Water Dispenser	COOK & COLD Water Dispenser
Model	RSHC-300	RSCC-300
Dimension	340 W x 350 D x 1010 H (mm)	
Weight	19 kg	18 kg
Current	5.50 A	
C O L D	Temp Control	AUTO
	Tank	3.5 L (Stainless Steel Tank)
	Capacity	5 L / h (2°C - 10°C)
H O T	Fuse	BIMETAL
	Temp Control	AUTO
	Tank	1.5 L (Stainless Steel Tank)
	Capacity	10 L / h (80°C - 95°C)
Power	115V/60Hz or 220V/50-60Hz	

Color

Off-white

Cabinet

Electric zinc-coated with high-polymer polyester resin metal sheets for the side panels with high impact, high gloss ABS materials for the top and front panels. Both materials can be easily cleaned and maintained. The sides have mounting holes for cup dispensers.

Refrigeration Unit

Air convection-cooled condenser, internally spring mounted, hermetically-sealed compressor with automatic overload protection. No need for lubrication. Environment-friendly, R134a refrigerant is accurately controlled by precise capillary tube.

Hot Water Tank *(for Model RSHC-300)*

1.5L capacity, type 304, stainless steel hot water tank with 500W internal heating element. Fast-draining, stainless steel tubing with drain nut. The tank is insulated with fire-retardant materials for good heat transfer and to save energy. The hot water is controlled between 80°C to 95°C by an automatic hot water thermostat. The system is protected by a heat limiter in the event of automatic thermostat failure. On-off switch is conveniently located at the back of the cooler.

Cold Water Tank

3.5L capacity type 304 stainless steel cold water tank with external copper refrigerant coil evaporator. Removable expanded polystyrene insulation. The cold water is controlled between 2°C to 10°C by an automatic cold water thermostat that is easily accessible at the back of the cooler.

Electrical

Available 100V 50/60Hz, 110-115V 60Hz and 220-240V 50/60Hz with fuse-protection. Unit comes with 1.80m power cord set with choice of plug. UL listed or CE certified.

Pilot Lamps

LED lights located at the display name plate of the front panel indicate whether the hot water and cold water are functioning.

Drip Tray

Made of high-impact ABS materials. Removable and concealed lift-out design with detachable anti-splash grill.

Faucets

Made of durable food-grade polypropylene. Self-closing, standard or child-safe faucets for hot water and standard self-closing faucets for room-temperature or cold water. Available cup or glass trip faucets.

Custom Logo

Company logo or brand name can be silk-screen printed on the display name plate, drip tray, or front panels.

Quality & Warranty

All surfaces in contact with water are food-grade and would resist any known sanitizers. This model is manufactured under strict quality control, 100% tested in the assembly line, and complies with UL and CE standards. Warranty is 18 months for the unit and 48 months for the refrigeration system. *(Please refer to the Warranty Card at the back of the User's Manual for details.)*



Clear Solutions. Pure Service.

P.O. Box 6416, Concord, CA 94524 USA

Tel 925.686.1864 / Fax 925.686.1865

sales@americanultrafil.com / www.americanultrafil.com