

Ultra Water Coolers

One of the most elegant bottled water coolers in the industry that dispenses hot and cold or room-temperature and cold water. Our Ultra bottled water coolers are ideal for homes, offices, schools, workshops and showrooms.

Available in a standard, free-standing model or as a counter top unit.



MODELS ▶

- USHC-100 Hot & Cold Standard
- USCC-100 Cook & Cold Standard
- UHC-100 Hot & Cold Counter Top
- UCC-100 Cook & Cold Counter Top

Bottle and cup dispenser sold separately.

*Enjoy Refreshing
& Pure Water Everyday!*



Clear Solutions. Pure Service.



Product Specifications & Features

Ultra

STANDARD MODEL		
Product Name	HOT & COLD Water Dispenser	COOK & COLD Water Dispenser
Model	USHC-100	USCC-100
Dimension	310 W x 310 D x 950 H (mm)	
Weight	19 kg	17 kg
Current	5.50 A	
C O L D	Temp Control	AUTO
	Tank	4 L
	Capacity	5 L / h (5 °C - 12 °C)
H O T	Fuse	BIMETAL
	Temp Control	AUTO
	Tank	2 L
	Capacity	10 L / h (80 °C - 90 °C)
Power	220V/1P/50-60Hz or 110V/1P/50-60Hz	

COUNTER TOP MODEL		
Product Name	HOT & COLD Water Dispenser	COOK & COLD Water Dispenser
Model	UCHC-100	UCCC-100
Dimension	310 W x 310 D x 543 H (mm)	
Weight	14 kg	12 kg
Current	5.50 A	
C O L D	Temp Control	AUTO
	Tank	4 L
	Capacity	5 L / h (5 °C - 12 °C)
H O T	Fuse	BIMETAL
	Temp Control	AUTO
	Tank	2 L
	Capacity	10 L / h (80 °C - 90 °C)
Power	220V/1P/50-60Hz or 110V/1P/50-60Hz	

Color

Off-white

Cabinet

High impact, high gloss ABS materials for the top and front panels. Electric zinc-coated with high-polymer, polyester resin metal sheets for side panels. Both materials can be easily cleaned and maintained. The sides have mounting holes for cup dispensers.

Refrigeration Unit

Air-convective-cooled condenser, internally spring mounted, hermetically-sealed compressor with automatic overload protection. No need for lubrication. Environment-friendly, R134a refrigerant is accurately controlled by a precise capillary tube.

Hot Water Tank *(for Models USHC-100 & UCHC-100)*

2L capacity, type 304 stainless steel hot water tank with type 316 stainless steel 500W internal heating element. Fast-draining stainless steel tubing with drain nut. Tank is insulated with fire-retardant materials for good heat transfer and to save energy. The hot water is controlled between 80°C to 90°C by an automatic hot water thermostat. The system is protected by a heat limiter in the event of automatic thermostat failure. On-off switch is conveniently located at the central control panel at the side of the cabinet.

Cold Water Tank

4L capacity type 304 stainless steel cold water tank with external copper refrigerant coil evaporator. Removable expanded polystyrene insulation. The cold water is controlled between 5°C to 12°C. by an automatic cold water thermostat that is easily accessible at the central control panel.

Electrical

Available 100V 50/60Hz, 110-115V 60Hz and 220-240V 50/60Hz with fuse-protection. Unit comes with 1.80m power cord set with choice of plug. UL Listed or CE certified.

Pilot Lamps

LED lights located at the display name plate of the front panel indicate whether the hot water and cold water are functioning.

Central Control Panel

This is a special feature of the Ultra cooler that centrally positions the on/off switch, fuse, cold control, spare fuse, and electric wiring diagram.

Drip Tray

Made of high-impact ABS materials. Removable and concealed lift-out design with detachable, anti-splash grill.

Faucets

Made of durable, food-grade polypropylene. Self-closing standard or child-safe faucets for hot water and standard, self-closing faucets for room-temperature or cold water.

Custom Logo

Company logo or brand name can be silk-screen printed on the display name plate, drip tray, or front panels.

Quality & Warranty

All surfaces in contact with water are food-grade and would resist any known sanitizers. This model is manufactured under strict quality control, 100% tested in the assembly line, and complies with UL and CE standards. Warranty is 18 months for the unit and 48 months for the refrigeration system. *(Please refer to the Warranty Card at the back of the User's Manual for details.)*



Clear Solutions. Pure Service.

P.O. Box 6416, Concord, CA 94524 USA

Tel 925.686.1864 / Fax 925.686.1865

sales@americanultrafil.com / www.americanultrafil.com